



www.fabtechmotorsports.com

4331 EUCALYPTUS AVE. CHINO, CA. 91710

PHONE 909-597-7800 FAX 909-597-7185

1984-2001 JEEP XJ 4WD

FTS2097 REAR SHACKLE KIT

PARTS LIST:

- 2 Ea. FT2097 Lift Shackle**
- 4 Ea. FT1034 Bushings**
- 2 Ea. FT2097-4 Shackle Sleeve**
- 2 Ea. 10mm-1.5 x 20mm Bolt**
- 2 Ea. 10mm Flat Washer**
- 1 Ea. FTLOCK Thread Locking Compound**
- 2 Ea. FT84 Grease Fitting**
- 1 Ea. FTLUBE Lube**

Tool List: (Not Included)

Floor Jack

Jack Stands


Assorted Metric and S.A.E Sockets & Allen Wrenches

READ ALL INSTRUCTIONS THOROUGHLY FROM START TO FINISH BEFORE BEGINNING INSTALLATION!

CHECK ALL PARTS INCLUDED IN THIS KIT TO THE PARTS LIST ABOVE BEFORE BEGINNING INSTALLATION OF THIS KIT. IF ANY PIECES ARE MISSING, CONTACT FABTECH AT 909-597-7800

INSTRUCTIONS:

- | | |
|---|--|
| <ol style="list-style-type: none">1. Disconnect the negative terminal on the battery. Jack up the rear end of the truck and support the frame rails with jack stands. Using a floor jack support the rear axle enough so it is not hanging from the truck. <u>NEVER WORK UNDER AN UNSUPPORTED VEHICLE!</u> Remove the rear tires.2. Working from both sides of the truck, remove the rear shocks and discard, and save hardware.3. Locate the rear shackles and remove the bolts securing them to the leaf springs, than remove the bolts securing the | <p>shackles to the frame. Discard the shackles and save the hardware.</p> <ol style="list-style-type: none">4. Locate the FT2097 shackle, press two bushings and one sleeve into the barrel on the shackles. Lube the bushings and sleeves with the supplied tube of silicon lube. Next install one of the supplied grease fittings into each shackle. Do not grease the shackle at the grease fitting at this time.5. Using the original hardware attach the lift shackle to the frame pocket then to the leaf spring. Leave bolts loose at this time. SEE PHOTO ON NEXT PAGE. |
|---|--|



6. Locate the factory lower rear bumper bolts. Remove and discard the bolts. Locate the supplied 10mm x 20mm bolt and washer and install where the previous bumper bolt was removed. Use a small amount of the supplied thread lock compound on the bumper bolts before installing.

7. Install the correct length shocks onto the truck.
8. Using a grease gun, grease the grease fittings on both shackles.
9. Reinstall the rear tires and torque the lugs to factory specifications. The factory torque specifications can be found in your owners manual.
10. Remove the jack stands and set the truck back onto the ground. Check the torque on all fasteners.
11. Torque all shackle bolts to 90 ft. lbs.

RETORQUE ALL NUTS, BOLTS AND LUGS AFTER 50 MILES AND PERIODICALLY THEREAFTER.

For technical assistance call: 909-597-7800

Product Warranty and Warnings-

Fabtech provides a Limited Lifetime Warranty to the original retail purchaser who owns the vehicle, on which the product was originally installed, for defects in workmanship and materials.

The Limited Lifetime Warranty excludes the following Fabtech items; bushings, bump stops, ball joints, tie rod ends, limiting straps, cross shafts, heim joints. These parts are subject to wear and are not considered defective when worn. They are warranted for 60 days from the date of purchase for defects in workmanship.

Take apart shocks are considered a serviceable shock with a one year warranty on leakage only. Service seal kits are available separately for future maintenance. All other shocks are covered under our Limited Lifetime Warranty.

Fabtech does not warrant any product for finish, alterations, modifications and/or installation contrary to Fabtech's instructions. Alterations to the finish of the parts including but not limited to painting, powdercoating, plating and/or welding will void all warranties. Some finish damage may occur to parts during shipping which is considered normal and is not covered under warranty.

Fabtech products are not designed nor intended to be installed on vehicles used in race applications or for racing purposes or for similar activities. (A "RACE" is defined as any contest between two or more vehicles, or any contest of one or more vehicle against the clock, whether or not such contest is for a prize). This warranty does not include coverage for police or taxi vehicles, race vehicles, or vehicles used for government or commercial purposes. Also excluded from this warranty are sales outside of the United States of America.

Installation of most suspension products will raise the center of gravity of the vehicle and will cause the vehicle to handle differently than stock. It may increase the vehicle's susceptibility to a rollover, on road and off road, at all speeds. Extreme care should be taken to operate the vehicle safely at all times to prevent rollover or loss of control resulting in serious injury or death. Fabtech front end Desert Guards may impair the deployment or operation of vehicles equipped with supplemental restraining systems/air bag systems and should not be installed if the vehicle is equipped as so.

Fabtech makes every effort to ensure suspension product compatibility with all vehicles listed in the catalog, but due to unknown auto manufacturers production changes and/or inconsistencies by the auto manufacturer, Fabtech cannot be responsible for 100% compatibility, including the fitment of tire and wheel sizes listed. The Tire and Wheel sizes listed in Fabtech's catalog are only a guideline for street driving with noted fender trimming. Fabtech is not responsible for damages to the vehicle's body or tires.

Fabtech's obligation under this warranty is limited to the repair or replacement, at Fabtech option, of the defective product only. All costs of removal, installation or re-installation, freight charges, incidental or consequential damages are expressly excluded from this warranty. Fabtech is not responsible for damages and/or warranty of other vehicle parts related or non related to the installed Fabtech product. This warranty is expressly in lieu of all other warranties expressed or implied. This warranty shall not apply to any product that has been subject to accident, negligence, alteration, abuse or misuse as determined by Fabtech.

Fabtech suspension components must be installed as a complete system including shocks as shown in our current catalog. All warranties will become void if Fabtech parts are combined and/or substituted with other aftermarket suspension products. Combination and/or substitution of other aftermarket suspension parts may cause premature wear and/or product failure resulting in an accident causing injury or death. Fabtech does not warrant products not manufactured by Fabtech.

Installation of Fabtech product may void the vehicles factory warranty; it is the consumer's responsibility to check with their local vehicle's dealer for warranty disposition before the installation of the product.

It is the responsibility of the distributor and/or the retailer to review all warranties and warnings of Fabtech products with the consumer prior to purchase.

Fabtech reserves the right to supercede, discontinue, change the design, finish, part number and, or application of parts when deemed necessary without written notice. Fabtech is not responsible for misprints or typographical errors within the catalog or price sheet.