



## ***Installation Instructions***

### ***Hummer H2 Rear Trac Bar Bracket***

***2003-2008 Hummer H2 SUV / SUT***

**FTS21079BK**

	<b>FTS21079</b>	<b>H2 Track Bar Replacement Kit</b>
<b>Qty</b>	<b>Part #</b>	<b>Description</b>
1	FT20384BK	Track Bar Bracket
1	FT20416	Hdwr Sub-Assembly Kit

	<b>FT20416</b>	<b>Hdwr Sub-Assembly Kit</b>
<b>Qty</b>	<b>Part #</b>	<b>Description</b>
2	50000005081	1/2" SAE Washer
1	50130004152	1/2"-13 C-lock Nut
1	50131251081	1/2"-13 x 1-1/4 Hex bolt
4	56000005081	9/16" SAE Washer
2	56120004182	9/16"-12 C-lock Nut
1	56121251081	9/16"-12 x 1-1/4 Hex bolt
1	56123251081	9/16"-12 x 3-1/4 Hex bolt
2	FT21079i	Instruction Sheet



### ***2003-2008 Hummer H2 SUV***

#### ***TOOL LIST: (NOT INCLUDED)***

- **FLOOR JACK & JACK STANDS**
- **ASSORTED METRIC AND S.A.E SOCKETS, & WRENCHES**
- **TORQUE WRENCH**
- **DRILL WITH ASSORTED BITS**

### **BEFORE YOU BEGIN INSTALLATION PLEASE READ THE FOLLOWING:**

CHECK ALL PARTS INCLUDED IN THIS KIT TO THE PARTS LIST ABOVE BEFORE BEGINNING INSTALLATION OF THE KIT. IF ANY PIECES ARE MISSING, CONTACT FABTECH AT 909-597-7800

READ ALL INSTRUCTIONS THOROUGHLY FROM START TO FINISH BEFORE BEGINNING INSTALLATION! IF THESE INSTRUCTIONS ARE NOT PROPERLY FOLLOWED, SEVERE FRAME, DRIVELINE AND / OR SUSPENSION DAMAGE MAY RESULT.



DO NOT ALTER THE FINISH OF THESE COMPONENTS, EXAMPLE- CHROMING, ZINC PLATING OR PAINTING. CHANGING THE FINISH CAN CAUSE STRUCTURAL FATIGUE OF COMPONENTS.

SUSPENSION SYSTEM MUST BE INSTALLED WITH FABTECH SHOCK ASBORBERS

VEHICLES THAT WILL RECEIVE OVERSIZED TIRES SHOULD CHECK BALL JOINTS, TIE RODS ENDS AND IDLER ARM EVERY 2500-5000 MILES FOR WEAR AND REPLACE AS NEEDED

### ***SUSPENSION INSTRUCTIONS:***

1. Disconnect the negative terminal on the battery. With the vehicle on level ground set the emergency brake and block the rear tires. Jack up the front end of the truck and support the frame rails with jack stands. **NEVER WORK UNDER AN UNSUPPORTED VEHICLE!** Remove the front tires.
2. Remove the lower pivot bolt that attaches the track bar to the bracket on the rear axle. Pull trac bar free from mount and save the hardware.
3. Slide the Trac Bar Bracket FT20384 into the original axle trac bar mount. Place the supplied 9/16" x 3 1/4" bolt, with a flat washer, through the original hole, followed by another flat washer and a c-lock nut. Make sure that the bracket is flat against the factory mount and tighten the 9/16" bolt.
4. Next, mark the 1/2" hole that is in the center of the bracket to the mount. Using a drill with a 1/2" bit, make a new mounting hole in the mount. Use the supplied 1/2 x 1 1/4" bolt and hardware to attach the new bracket to the mount. Next, mark the 9/16" hole that is in the face of the bracket to the mount. Using a drill with a 9/16" bit, make a new mounting hole in the mount. Use the supplied 9/16" x 1 1/4" bolt and hardware to attach the new bracket to the mount. Torque the 1/2" hardware to 75 ft. lbs & the 9/16" hardware to 95 ft. lbs. SEE DIAGRAMS ON LAST PAGES OF THE INSTRUCTIONS



5. Remove the jack stands and set the truck back onto the ground. Check the torque on all fasteners.
6. Check the front-end alignment and set to the factory specifications. Re-adjust headlights.

**RETORQUE ALL NUTS, BOLTS AND LUGS AFTER 50 MILES AND PERIODICALLY THEREAFTER.**  
For technical assistance call: 909-597-7800

## Product Warranty and Warnings-

Fabtech provides a Limited Lifetime Warranty to the original retail purchaser who owns the vehicle, on which the product was originally installed, for defects in workmanship and materials.

The Limited Lifetime Warranty excludes the following Fabtech items; bushings, bump stops, ball joints, tie rod ends, limiting straps, cross shafts, heim joints. These parts are subject to wear and are not considered defective when worn. They are warranted for 60 days from the date of purchase for defects in workmanship.

Take apart shocks are considered a serviceable shock with a one year warranty on leakage only. Service seal kits are available separately for future maintenance. All other shocks are covered under our Limited Lifetime Warranty.

Fabtech does not warrant any product for finish, alterations, modifications and/or installation contrary to Fabtech's instructions. Alterations to the finish of the parts including but not limited to painting, powdercoating, plating and/or welding will void all warranties. Some finish damage may occur to parts during shipping which is considered normal and is not covered under warranty.

Fabtech products are not designed nor intended to be installed on vehicles used in race applications or for racing purposes or for similar activities. (A "RACE" is defined as any contest between two or more vehicles, or any contest of one or more vehicle against the clock, whether or not such contest is for a prize). This warranty does not include coverage for police or taxi vehicles, race vehicles, or vehicles used for government or commercial purposes. Also excluded from this warranty are sales outside of the United States of America.

Installation of most suspension products will raise the center of gravity of the vehicle and will cause the vehicle to handle differently than stock. It may increase the vehicle's susceptibility to a rollover, on road and off road, at all speeds. Extreme care should be taken to operate the vehicle safely at all times to prevent rollover or loss of control resulting in serious injury or death. Fabtech front end Desert Guards may impair the deployment or operation of vehicles equipped with supplemental restraining systems/air bag systems and should not be installed if the vehicle is equipped as so.

Fabtech makes every effort to ensure suspension product compatibility with all vehicles listed in the catalog, but due to unknown auto manufacturers production changes and/or inconsistencies by the auto manufacturer, Fabtech cannot be responsible for 100% compatibility, including the fitment of tire and wheel sizes listed. The Tire and Wheel sizes listed in Fabtech's catalog are only a guideline for street driving with noted fender trimming. Fabtech is not responsible for damages to the vehicle's body or tires.

Fabtech's obligation under this warranty is limited to the repair or replacement, at Fabtech option, of the defective product only. All costs of removal, installation or re-installation, freight charges, incidental or consequential damages are expressly excluded from this warranty. Fabtech is not responsible for damages and/or warranty of other vehicle parts related or non related to the installed Fabtech product. This warranty is expressly in lieu of all other warranties expressed or implied. This warranty shall not apply to any product that has been subject to accident, negligence, alteration, abuse or misuse as determined by Fabtech.

Fabtech suspension components must be installed as a complete system including shocks as shown in our current catalog. All warranties will become void if Fabtech parts are combined and/or substituted with other aftermarket suspension products. Combination and/or substitution of other aftermarket suspension parts may cause premature wear and/or product failure resulting in an accident causing injury or death. Fabtech does not warrant products not manufactured by Fabtech.

Installation of Fabtech product may void the vehicles factory warranty; it is the consumer's responsibility to check with their local vehicle's dealer for warranty disposition before the installation of the product.

It is the responsibility of the distributor and/or the retailer to review all warranties and warnings of Fabtech products with the consumer prior to purchase.

Fabtech reserves the right to supercede, discontinue, change the design, finish, part number and, or application of parts when deemed necessary without written notice. Fabtech is not responsible for misprints or typographical errors within the catalog or price sheet.