



Installation Instructions

FTS8016

**1994-2002 Dodge 4WD
Dual Steering Stabilizer Kit**

PARTS LIST-

- 2- Steering Stabilizer
- 1- Axle Bracket
- 2- Tie Rod Bracket
- 2- U-Bolts For Axle Bracket (large)
- 4- U-Bolts For Tie Rod Bracket (small)
- 2- Shock Pins W/ Hardware.
- 2- Stem Bushing Kit

TOOL LIST- (NOT INCLUDED)

- Assorted Metric & SAE Sockets & Wrenches
- Torque Wrench

READ ALL INSTRUCTIONS THOROUGHLY FROM START TO FINISH BEFORE BEGINNING INSTALLATION! IF THESE INSTRUCTIONS ARE NOT PROPERLY FOLLOWED, SEVERE FRAME, DRIVELINE AND / OR SUSPENSION DAMAGE MAY RESULT.

CHECK FOR FRAME AND SUSPENSION DAMAGE PRIOR TO INSTALLTION. THIS KIT DOES NOT REQUIRE WELDING FOR INSTALLATION. DO NOT WELD ANY OF THESE COMPONENTS. THE INSTALLATION OF THIS KIT SHOULD BE PERFORMED BY A PROFESSIONAL MECHANIC.


CHECK ALL PARTS INCLUDED IN THIS KIT TO THE PARTS LIST ABOVE BEFORE BEGINNING INSTALLATION OF THE KIT. IF ANY PIECES ARE MISSING, CONTACT FABTECH AT 909-597-7800.

THIS KIT WILL NOT WORK ON 2500 & 3500 MODEL TRUCKS WITH AN 8800 GVW RATING.


INSTALLATION-

1. Disconnect the negative terminal on the battery. Position the front tires of the vehicle to straight ahead.
2. Locate the factory steering stabilizer and remove it from the truck. Discard the stabilizer.


3. Locate the supplied axle bracket and two large u-bolts. Attach the axle bracket to the center of the axle using the large u-bolts and the supplied hardware.




4. Locate the two supplied shock pins. Using the supplied hardware attach the shock pins to the axle bracket so they are facing upwards. SEE PHOTO BELOW.



5. Locate the two supplied tie rod end brackets. Using the supplied small u-bolts and hardware loosely attach one tie rod end bracket to the driver side and one to the passenger side tie rod end. SEE PHOTOS BELOW.



Passenger Side



Driver Side

6. Working from the driver side of the truck, locate one of the supplied steering stabilizers and pull the shaft out 4 ½". Attach the side with the barrel bushing to the axle bracket than the other end to the tie rod bracket using the supplied hardware. Use care not to change the amount of shaft previously measured when attaching. Torque the tie rod end u-bolts to 30 ft. lbs. Tighten both end bushings of the stabilizers until the bushings begin to squeeze out. Repeat on the passenger Side of the truck. SEE COMPLETED PHOTO BELOW.



7. Recheck each nut and bolt for proper torque.
8. Turn the wheels left to right and check for proper turning radius. Adjust the steering stabilizer tie rod end bracket to achieve left to right turning radius as required.

RETORQUE ALL NUTS, BOLTS AND LUGS AFTER 50 MILES AND PERIODICALLY THEREAFTER.

For technical assistance call: 909-597-7800

Product Warranty and Warnings-

Fabtech provides a Limited Lifetime Warranty to the original retail purchaser who owns the vehicle, on which the product was originally installed, for defects in workmanship and materials.

The Limited Lifetime Warranty excludes the following Fabtech items; bushings, bump stops, ball joints, tie rod ends, limiting straps, cross shafts, heim joints. These parts are subject to wear and are not considered defective when worn. They are warranted for 60 days from the date of purchase for defects in workmanship.

Take apart shocks are considered a serviceable shock with a one year warranty on leakage only. Service seal kits are available separately for future maintenance. All other shocks are covered under our Limited Lifetime Warranty.

Fabtech does not warrant any product for finish, alterations, modifications and/or installation contrary to Fabtech's instructions. Alterations to the finish of the parts including but not limited to painting, powdercoating, plating and/or welding will void all warranties. Some finish damage may occur to parts during shipping which is considered normal and is not covered under warranty.

Fabtech products are not designed nor intended to be installed on vehicles used in race applications or for racing purposes or for similar activities. (A "RACE" is defined as any contest between two or more vehicles, or any contest of one or more vehicle against the clock, whether or not such contest is for a prize). This warranty does not include coverage for police or taxi vehicles, race vehicles, or vehicles used for government or commercial purposes. Also excluded from this warranty are sales outside of the United States of America.

Installation of most suspension products will raise the center of gravity of the vehicle and will cause the vehicle to handle differently than stock. It may increase the vehicle's susceptibility to a rollover, on road and off road, at all speeds. Extreme care should be taken to operate the vehicle safely at all times to prevent rollover or loss of control resulting in serious injury or death. Fabtech front end Desert Guards may impair the deployment or operation of vehicles equipped with supplemental restraining systems/air bag systems and should not be installed if the vehicle is equipped as so.

Fabtech makes every effort to ensure suspension product compatibility with all vehicles listed in the catalog, but due to unknown auto manufacturers production changes and/or inconsistencies by the auto manufacturer, Fabtech cannot be responsible for 100% compatibility, including the fitment of tire and wheel sizes listed. The Tire and Wheel sizes listed in Fabtech's catalog are only a guideline for street driving with noted fender trimming. Fabtech is not responsible for damages to the vehicle's body or tires.

Fabtech's obligation under this warranty is limited to the repair or replacement, at Fabtech option, of the defective product only. All costs of removal, installation or re-installation, freight charges, incidental or consequential damages are expressly excluded from this warranty. Fabtech is not responsible for damages and/or warranty of other vehicle parts related or non related to the installed Fabtech product. This warranty is expressly in lieu of all other warranties expressed or implied. This warranty shall not apply to any product that has been subject to accident, negligence, alteration, abuse or misuse as determined by Fabtech.

Fabtech suspension components must be installed as a complete system including shocks as shown in our current catalog. All warranties will become void if Fabtech parts are combined and/or substituted with other aftermarket suspension products. Combination and/or substitution of other aftermarket suspension parts may cause premature wear and/or product failure resulting in an accident causing injury or death. Fabtech does not warrant products not manufactured by Fabtech.

Installation of Fabtech product may void the vehicles factory warranty; it is the consumer's responsibility to check with their local vehicle's dealer for warranty disposition before the installation of the product.

It is the responsibility of the distributor and/or the retailer to review all warranties and warnings of Fabtech products with the consumer prior to purchase.

Fabtech reserves the right to supercede, discontinue, change the design, finish, part number and, or application of parts when deemed necessary without written notice. Fabtech is not responsible for misprints or typographical errors within the catalog or price sheet.