



www.fabtechmotorsports.com

**4331 EUCALYPTUS AVE. CHINO, CA. 91710
PHONE 909-597-7800 FAX 909-597-7185**

**Transmission Drop Bracket
FTS93008BK
2007-2010 Dodge Ram 2500 4wd
6.7L Diesel w/ Automatic Transmission**

Parts List

Qu a	Part #	Description
1	FT44110	Transmission Bracket
1	FTS419	Shim Kit
1	FT44186	Hardware for Shim Kit
1	FT93008i	Instruction Sheet

Tool List: (Not Included)

- Jack w/ Jack stands
- Assorted S.A.E Sockets & Combination Wrenches
- Transmission Jack
- Torque Wrench

THIS DROP BRACKET WILL ONLY WORK WITH TRUCKS EQUIPPED THE 6.7 L DIESEL ENGINE AND AUTOMATIC TRANSMISSION.

THIS BRACKET IS DESIGNED FOR USE ONLY WITH A FABTECH 4.5" or 6" SUSPENSION SYSTEM

READ ALL INSTRUCTIONS THOROUGHLY FROM START TO FINISH BEFORE BEGINNING INSTALLATION!

CHECK ALL PARTS INCLUDED IN THIS KIT TO THE PARTS LIST ABOVE BEFORE BEGINNING INSTALLATION OF THIS KIT. IF ANY PIECES ARE MISSING, CONTACT FABTECH AT 909-597-7800.

THE PICTURES IN THIS INSTRUCTION SHEET ARE USED IN MULTIPLE TRANSMISSION BRACKETS KITS. THEY ARE TO BE USED AS A REFERENCE ONLY.

INSTRUCTIONS:

1. Disconnect the negative terminal on the battery. With the vehicle on level ground, set the emergency brake and block the rear tires. Jack up the front end of the truck and support the frame rails with jack stands just behind the front bumper. **NEVER WORK UNDER AN UN-SUPPORTED VEHICLE.**
2. Support the transfer case and transmission with a transmission or floor jack. Remove the transfer case skid plate (if equipped) and save with the hardware. SEE PHOTOS BELOW




3. Remove the two transmission mount nuts from the crossmember. Carefully raise the transmission and remove the four crossmember bolts from the frame saving the crossmember and the hardware. SEE PHOTOS IN NEXT COLUMN




4. Remove the three bolts that hold the factory trans bracket to the trans mount. Remove the four bolts that secure the trans mount to the transmission. Raise the

jack just enough so that the stock mount can be removed. SEE PHOTO ON NEXT PAGE.



5. Locate FT44110 Drop Transmission Bracket and factory hardware. Install the new mount onto the trans and then the mount onto the trans bracket. Re-install the crossmember. Lower the transmission and re-install the factory flange nuts securing the trans mount to the crossmember. Tighten all of the nuts and bolts. Lower the jack that was used to support the transmission and torque all of the hardware to 65 ft. lbs. SEE PHOTOS BELOW.



RETORQUE ALL NUTS, BOLTS AND LUGS AFTER 50 MILES AND PERIODICALLY THEREAFTER
For technical assistance call: 909-597-7800

Product Warranty and Warnings-

Fabtech provides a Limited Lifetime Warranty to the original retail purchaser who owns the vehicle, on which the product was originally installed, for defects in workmanship and materials.

The Limited Lifetime Warranty excludes the following Fabtech items; bushings, bump stops, ball joints, tie rod ends, limiting straps, cross shafts, heim joints. These parts are subject to wear and are not considered defective when worn. They are warranted for 60 days from the date of purchase for defects in workmanship.

Take apart shocks are considered a serviceable shock with a one year warranty on leakage only. Service seal kits are available separately for future maintenance. All other shocks are covered under our Limited Lifetime Warranty.

Fabtech does not warrant any product for finish, alterations, modifications and/or installation contrary to Fabtech's instructions. Alterations to the finish of the parts including but not limited to painting, powdercoating, plating and/or welding will void all warranties. Some finish damage may occur to parts during shipping which is considered normal and is not covered under warranty.

Fabtech products are not designed nor intended to be installed on vehicles used in race applications or for racing purposes or for similar activities. (A "RACE" is defined as any contest between two or more vehicles, or any contest of one or more vehicle against the clock, whether or not such contest is for a prize). This warranty does not include coverage for police or taxi vehicles, race vehicles, or vehicles used for government or commercial purposes. Also excluded from this warranty are sales outside of the United States of America.

Installation of most suspension products will raise the center of gravity of the vehicle and will cause the vehicle to handle differently than stock. It may increase the vehicle's susceptibility to a rollover, on road and off road, at all speeds. Extreme care should be taken to operate the vehicle safely at all times to prevent rollover or loss of control resulting in serious injury or death. Fabtech front end Desert Guards may impair the deployment or operation of vehicles equipped with supplemental restraining systems/air bag systems and should not be installed if the vehicle is equipped as so.

Fabtech makes every effort to ensure suspension product compatibility with all vehicles listed in the catalog, but due to unknown auto manufacturers production changes and/or inconsistencies by the auto manufacturer, Fabtech cannot be responsible for 100% compatibility, including the fitment of tire and wheel sizes listed. The Tire and Wheel sizes listed in Fabtech's catalog are only a guideline for street driving with noted fender trimming. Fabtech is not responsible for damages to the vehicle's body or tires.

Fabtech's obligation under this warranty is limited to the repair or replacement, at Fabtech option, of the defective product only. All costs of removal, installation or re-installation, freight charges, incidental or consequential damages are expressly excluded from this warranty. Fabtech is not responsible for damages and/or warranty of other vehicle parts related or non related to the installed Fabtech product. This warranty is expressly in lieu of all other warranties expressed or implied. This warranty shall not apply to any product that has been subject to accident, negligence, alteration, abuse or misuse as determined by Fabtech.

Fabtech suspension components must be installed as a complete system including shocks as shown in our current catalog. All warranties will become void if Fabtech parts are combined and/or substituted with other aftermarket suspension products. Combination and/or substitution of other aftermarket suspension parts may cause premature wear and/or product failure resulting in an accident causing injury or death. Fabtech does not warrant products not manufactured by Fabtech.

Installation of Fabtech product may void the vehicles factory warranty; it is the consumer's responsibility to check with their local vehicle's dealer for warranty disposition before the installation of the product.

It is the responsibility of the distributor and/or the retailer to review all warranties and warnings of Fabtech products with the consumer prior to purchase.

Fabtech reserves the right to supercede, discontinue, change the design, finish, part number and, or application of parts when deemed necessary without written notice. Fabtech is not responsible for misprints or typographical errors within the catalog or price sheet.