



4331 EUCALYPTUS AVE. ~~ CHINO, CA 91710
909-597-7800 Fax 909-597-7185

FTR10057BK
TROPHY KART NERF BAR (PAIR)

	FTR10057BK	Trophy kart Nerf Bars
Qty.	Part #	Description
1	FT95091BK	Nerf bar driver upper
1	FT95090BK	Nerf bar pass upper
1	FT95089BK	Nerf bar driver lower
1	FT95088BK	Nerf bar pass lower
2	FT95092BK	Nerf bar tube clamp BLK
8	FT95093	Bumper clamp
1	FT95144	Hdwr Sub-Assembly Kit

	FT95144	Hdwr Sub-Assembly Kit
Qua	Part #	Description
2	FT90090	.375 x 2.5 Hitch pin w/ cotter pin
4	37162751081	Screw 3/8-16 x 2 3/4 bolt
4	37160003052	Nut 3/8-16 Nylock nut
8	37000005052	Washer 3/8
16	31181501081	5/16-18 x 1 1/2 bolt
16	31180003352	5/16-18 stover nut
32	31000005052	Washer 5/16
2	FTR10057i	Instructions

TOOL LIST:

- o Assorted Metric Wrenches
- o Phillips & Standard Screw Drivers

& Standard

WARNING


READ ALL INSTRUCTIONS THOROUGHLY FROM START TO FINISH BEFORE BEGINNING INSTALLATION.

CHECK ALL PARTS INCLUDED IN THIS KIT TO THE PARTS LIST ABOVE BEFORE BEGINNING INSTALLATION OF THIS KIT. IF ANY PARTS ARE MISSING, CONTACT FABTECH AT 909-597-7800.


DO NOT ALTER THE FINISH OF THESE COMPONENTS, EXAMPLE- CHROMING, ZINC PLATING OR PAINTING. CHANGING THE FINISH CAN CAUSE STRUCTURAL FATIGUE OF COMPONENTS.

INSTALLATION INSTRUCTIONS:


1. Locate FT95088BK Nerf bar passenger lower. Start on passenger side just in front of the rear shock. Locate P/N FT95093 clamp and the 5/16 bolts, nuts and washers. Clamp nerf bar at the two points shown above loosely. SEE PHOTO BELOW.



2. Locate the front of the lower nerf bar clamp on the lower tube of the kart and install the clamp. SEE PHOTO BELOW.




3. Locate P/N FT95090BK and install the bottom of the upper mount into the lower mount using the supplied 5/16 bolts, washers and nuts leave loose. SEE PHOTO IN NEXT COLUMN.



4. Locate P/N FT95092BK Nerf bar tube clamp and FT90090 Hitch pin. Attach the tube clamp to the upper nerf bar with the hitch pin and line it up with the tube on the roll cage. Clamp the mount loosely. SEE PHOTO BELOW.



5. Make sure all the mounting points are lined up and tighten all the bolts. Torque to 14 ft. lbs.
6. Repeat all the steps above on driver side. SEE PHOTO ON NEXT PAGE FOR FINISHED VIEW.



RETORQUE ALL NUTS, BOLTS AND LUGS AFTER 50 MILES AND PERIODICALLY THEREAFTER.
For technical assistance call: 909-597-7800

Product Warranty and Warnings-

Fabtech provides a Limited Lifetime Warranty to the original retail purchaser who owns the vehicle, on which the product was originally installed, for defects in workmanship and materials.

The Limited Lifetime Warranty excludes the following Fabtech items; bushings, bump stops, ball joints, tie rod ends, limiting straps, cross shafts, heim joints. These parts are subject to wear and are not considered defective when worn. They are warranted for 60 days from the date of purchase for defects in workmanship.

Take apart shocks are considered a serviceable shock with a one year warranty on leakage only. Service seal kits are available separately for future maintenance. All other shocks are covered under our Limited Lifetime Warranty.

Fabtech does not warrant any product for finish, alterations, modifications and/or installation contrary to Fabtech's instructions. Alterations to the finish of the parts including but not limited to painting, powdercoating, plating and/or welding will void all warranties. Some finish damage may occur to parts during shipping which is considered normal and is not covered under warranty.

Fabtech products are not designed nor intended to be installed on vehicles used in race applications or for racing purposes or for similar activities. (A "RACE" is defined as any contest between two or more vehicles, or any contest of one or more vehicle against the clock, whether or not such contest is for a prize). This warranty does not include coverage for police or taxi vehicles, race vehicles, or vehicles used for government or commercial purposes. Also excluded from this warranty are sales outside of the United States of America.

Installation of most suspension products will raise the center of gravity of the vehicle and will cause the vehicle to handle differently than stock. It may increase the vehicle's susceptibility to a rollover, on road and off road, at all speeds. Extreme care should be taken to operate the vehicle safely at all times to prevent rollover or loss of control resulting in serious injury or death. Fabtech front end Desert Guards may impair the deployment or operation of vehicles equipped with supplemental restraining systems/air bag systems and should not be installed if the vehicle is equipped as so.

Fabtech makes every effort to ensure suspension product compatibility with all vehicles listed in the catalog, but due to unknown auto manufacturers production changes and/or inconsistencies by the auto manufacturer, Fabtech cannot be responsible for 100% compatibility, including the fitment of tire and wheel sizes listed. The Tire and Wheel sizes listed in Fabtech's catalog are only a guideline for street driving with noted fender trimming. Fabtech is not responsible for damages to the vehicle's body or tires.

Fabtech's obligation under this warranty is limited to the repair or replacement, at Fabtech option, of the defective product only. All costs of removal, installation or re-installation, freight charges, incidental or consequential damages are expressly excluded from this warranty. Fabtech is not responsible for damages and/or warranty of other vehicle parts related or non related to the installed Fabtech product. This warranty is expressly in lieu of all other warranties expressed or implied. This warranty shall not apply to any product that has been subject to accident, negligence, alteration, abuse or misuse as determined by Fabtech.

Fabtech suspension components must be installed as a complete system including shocks as shown in our current catalog. All warranties will become void if Fabtech parts are combined and/or substituted with other aftermarket suspension products. Combination and/or substitution of other aftermarket suspension parts may cause premature wear and/or product failure resulting in an accident causing injury or death. Fabtech does not warrant products not manufactured by Fabtech.

Installation of Fabtech product may void the vehicles factory warranty; it is the consumer's responsibility to check with their local vehicle's dealer for warranty disposition before the installation of the product.

It is the responsibility of the distributor and/or the retailer to review all warranties and warnings of Fabtech products with the consumer prior to purchase.

Fabtech reserves the right to supercede, discontinue, change the design, finish, part number and, or application of parts when deemed necessary without written notice. Fabtech is not responsible for misprints or typographical errors within the catalog or price sheet.