



INSTALLATION INSTRUCTIONS

| FTS26131 | | TOYOTA TACOMA/4RUNNER DIFF DROP KIT |
|----------|---------|-------------------------------------|
| 1 | FT70393 | DIFF DROP BRACKET (DRIVER) |
| 1 | FT70394 | DIFF DROP BRACKET (PASS) |
| 1 | FT70415 | DIFF BRACKET (REAR) |

| FT70398 | | HARDWARE SUBASSEMBLY |
|---------|-----------|----------------------|
| 4 | FT1054 | BUSHING |
| 2 | FT70405 | SLEEVE |
| 2 | FT70414 | BUSHING |
| 1 | FT70415_5 | SLEEVE |
| 2 | FT70415_3 | WASHER |
| 1 | FTAS12 | STICKER |
| 1 | FTAS16 | DRIVER WARNING DECAL |
| 1 | FTREGCARD | REGISTRATION CARD |
| 1 | FT26131i | INSTRUCTIONS |

| FT70397 - HARDWARE KIT | | LOCATION |
|------------------------|-----------------------------|----------|
| 2 | M14-1.5 X 90MM HEX CAP BOLT | |
| 2 | M14 FLAT WASHER | |
| 2 | M14 SPLIT LOCK WASHER | |
| 2 | M16-1.5 NYLOCK NUT | |
| 2 | M16 FLAT WASHER | |

| FT70419 - HARDWARE KIT | | LOCATION |
|------------------------|-----------------------------|----------|
| 1 | M12-1.5 X 30MM HEX CAP BOLT | |
| 1 | M12-1.5 X 80MM HEX CAP BOLT | |
| 1 | M14-1.5 X 60MM HEX CAP BOLT | |
| 3 | M12 FLAT WASHER | |
| 1 | M12-1.5 NYLOCK NUT | |

2024-2025 TOYOTA TACOMA/4RUNNER 4WD DIFF DROP BRACKET KIT

FTS26131

NOTE: TO ORDER WEARABLE REPLACEMENT COMPONENTS DO NOT USE PART NUMBERS SHOWN ON THIS INSTRUCTION SHEET. GO TO FABTECH WEBSITE AND LOOK UP WEARABLE REPLACEMENT PARTS TO FIND THE PROPER PART NUMBER TO ORDER.

Fabtech Motorsports | 2213 Industrial Park Rd. Lancaster, SC 29720

Tech Line: 909-597-7800 | Web: www.fabtechmotorsports.com

- TOOL LIST -

Required Tools (Not Included)

Basic Hand Tools
Floor Jack
Jack Stands
Assorted Metric and S.A.E sockets, and Allen wrenches
Torque Wrench
Die Grinder w/ Cutoff Wheel or Sawzall

- PRE-INSTALLATION NOTES -

For technical assistance call: **909-597-7800** or e-mail: **info@fabtechmotorsports.com**

READ THIS BEFORE YOU BEGIN INSTALLATION -

Check all parts to the parts list above before beginning installation. If any parts are missing contact Fabtech at 909-597-7800 and a replacement part will be sent to you immediately.

This suspension and shocks have been designed to be installed on a stock vehicle.

Read all instructions thoroughly from start to finish before beginning the installation. If these instructions are not properly followed severe frame, driveline and / or suspension damage may occur.

Check your local city and state laws prior to the installation of this system for legality. Do not install if not legal in your area.

Prior to the installation of this suspension system perform a front end alignment and record. Do not install this system if the vehicle alignment is not within factory specifications. Check for frame and suspension damage prior to installation.

The installation of this suspension system should be performed by two professional mechanics. This suspension must be installed with Fabtech shock absorbers.

Installation of all fasteners requires the use of provided thread locking compound with proper torque values as indicated throughout the installation. Apply thread locking compound upon the final torque of the fastener.

WARNING- Installation of this system will alter the center of gravity of the vehicle and may increase roll over as compared to stock. Extreme care should be taken to operate the vehicle safely at all times to prevent rollover or loss of control resulting in serious injury or death.

Vehicles that receive oversized tires should check ball joints, uniballs, tie rods ends, pitman arm and idler arm every 2500-5000 miles for wear and replace as needed.

Verify differential fluid is at manufactures recommended level prior to kit installation. Installation of the kit will reposition the differential and the fill plug hole may be in a different position. (For example, if the manufacture recommends 3 quarts of fluid, make sure the diff has 3 quarts of fluid). Check your specific manual for correct amount of fluid.

Read all warnings and warranties on the last page of these instructions before starting installation.

FOOTNOTES -

-

- INSTRUCTIONS -


1. Disconnect the negative terminal on the battery. Jack up the front end of the truck and support the frame rails with jack stands. **NEVER WORK UNDER AN UNSUPPORTED VEHICLE!** Remove the front tires.




2. Support the front differential with a jack.

3. Remove the long nut attaching the rear differential mount to the frame crossmember.

4. Remove the front driver differential mount. Discard the (2) bolts that are used to mount the bracket to the diff housing. Save the factory hardware from the frame side.




5. Remove the front passenger differential mount. Save all factory hardware.



6. Locate the new driver side diff bracket (FT70393). Install (2) Bushings (FT1054) and (FT70405) sleeve.



7. Install the new diff bracket to the frame side using the factory hardware. Leave loose. Install the supplied M14 x 90mm bolts on the diff side.



8. Locate the Passenger side diff bracket (FT70394). Insert (2) FT1054 Bushings and a FT70405 Sleeve. Install the new pass diff bracket to the frame using the factory hardware. Then, install the factory bolts with the supplied M16 washers and nuts on the diff side. Leave Loose.



9. Using the appropriate jack, jack up the differential. Remove and discard the left side (closest to the frame) mounting bolt.




10. Lower the diff back down, allowing the diff to sit on the crossmember. Remove and discard the right side (closest to the motor) bolt. Jack the differential back up and remove the rear diff mount.



11. Locate the new rear differential bracket (FT70415). Install (FT70414) Bushings & (FT70415_5) Sleeve.



12. Install the supplied M14 x 60mm bolt and FT70415_3 (Washer) through the center hole of the new bracket. Install the new bracket to the diff using the supplied M12 x 30mm bolt for the left side and the M12 x 80mm bolt, nut and washers for the right side. Install FT70415_3 (Washer) on the top of the crossmember.



13. Lower the diff onto the crossmember.
Reinstall the long nut through the crossmember and thread onto the bolt.

- Torque the Driver, Passenger and rear differential bracket hardware to the specs below.

Torque the M12 bolt to 70 ft-lbs.

Torque the M14 bolt to 110 ft-lbs.

Torque the M16 bolt to 150 ft-lbs.

14. Install tires and wheels and torque lug nuts to wheel manufacturer's specifications.

15. Recheck all bolts for proper torque. **RE-TORQUE ALL NUTS, BOLTS AND LUGS AFTER 50 MILES AND PERIODICALLY THEREAFTER UNTIL TORQUE VALUES ARE RETAINED.**

16. Install Driver Warning Decal. Complete product registration card and mail to Fabtech in order to receive future safety and technical bulletins on this suspension.

17. Review all included warnings and warranties with consumer

For technical assistance call: **909-597-7800**



- Product Warranty & Warnings -

Fabtech provides a Limited Lifetime Warranty to the original retail purchaser who owns the vehicle, on which the product was originally installed, for defects in workmanship and materials.

The Limited Lifetime Warranty excludes the following Fabtech items; bushings, bump stops, ball joints, Uniball bearings, tie rod ends, limiting straps, cross shafts, heim joints and driveshafts. These parts are subject to wear and are not considered defective when worn. They are warranted for 60 days from the date of purchase for defects in workmanship.

Dirt Logic take apart shocks are considered a serviceable shock with a 1-year warranty against any manufacturer's defects. If a shock fails within the initial year of ownership, the owner must ship the shock to Fabtech for inspection and service. If after examination the shock is determined to have failed due to neglect, damage caused by improper installation, or any reason other than "normal wear and tear," the owner of the shock will be responsible for all service costs. Costs include labor, parts, and shipping. Service seal kits are available separately for future maintenance. All other shocks are covered under our Limited Lifetime Warranty.

Fabtech does not warrant any product for finish, alterations, modifications and/or installation contrary to Fabtech's instructions. Alterations to the finish of the parts including but not limited to painting, powder coating, plating and/or welding will void all warranties. Some finish damage may occur to parts during shipping, which is considered normal and is not covered under warranty.

Fabtech products are not designed nor intended to be installed on vehicles used in race applications or for racing purposes or for similar activities. This warranty does not include coverage for police, taxi, first responder vehicles, race vehicles, or vehicles used for government, commercial or fleet purposes. Also excluded from this warranty are sales outside of the United States of America.

Installation of most suspension products will raise the center of gravity of the vehicle and will cause the vehicle to handle differently than stock. It may increase the vehicle's susceptibility to a rollover, on road and off road, at all speeds. Extreme care should be taken to operate the vehicle safely at all times to prevent rollover or loss of control resulting in serious injury or death.

Oversized tires and wheels may decrease the vehicle's braking capacity. Drivers should always brake early and be aware of the increased the stopping distance of the vehicle. Drivers should adjust their driving habits to the effectiveness of the braking. Adjust your driving habits to these changes.

Failure to drive safely may result in serious injury or death to driver and passengers. Driver and passengers must ALWAYS wear your seat belts, avoid quick sharp turns and other sudden maneuvers